	TITLE: Operating Instructions for 2-7/8" Triple Port PBL		
	Document ID DSI-GL-75-006	Revision 4	Prepared By Suraj Varma DV
	Issue Date 13-10-2013	Revision Date 09-03-2017	Approved By Gernot Bauer

2-7/8" TRIPLE PORTED PBL BYPASS SYSTEM

OPERATING INSTRUCTIONS

RECEIVING PBL AT RIG SITE

1. On receipt of PBL Bypass Tools at Rig site, the tools should be checked for the following:
 - PBL Serial Numbers located on ID band below Ports on the Main Body.
 - Confirm rig end connections are as required.
 - Confirm Drop Ball Kit matches tool size and number.
 - Shearing pressures for Ball Seat (Deactivation Pressure) and Ports (Unlocking Pressure) are marked on tool and on Tech Sheet included in tool packet.
 - Confirm PBL Activation Ball will drift through entire drill string above PBL Tool.
 - Confirm PBL No-Go will allow passage of any required third party Activation Balls.
 - Drift the drop ball thru PBL prior to connecting BHA.
 - Remove tape covering PBL Ports prior to RIH.

2. The Drop Ball Kit that comes with each tool should contain;
 - 7 x 7/8" Torlon Activation Balls
 - 21 x 13/16" Steel De-Activation Balls

STATIC TEMPERATURE RATING OF ACTIVATION BALLS

- Torlon ball (black colour) - 450 deg F (230 deg C)


MAKE UP and TESTING THE PBL AT THE SURFACE (Recommended)

1. Pick up the tool and make up the Main Body to the Ball Catcher Sub.
 - Ensure that the Sleeve, is in the closed position by looking through the Port on the side of the tool.
 - Ensure that the Ball Catcher cage in Ball Catcher Sub has the bevelled end facing up and no-go cage facing down.
 - Make-up torque is the same as the rotary shoulder thread connection. **(Do not Over Torque)**.

2. Lower the BHA into the hole ensuring that the Ports are below the rotary table.

3. Drop one (1) x **7/8"** Activation Ball to activate the tool.
 - It is recommended to fill up the drill string with fluid prior to dropping the Activation Ball.
 - Make-up Kelly to PBL Tool.

4. Engage the pump slowly and watch for the Sleeve opening and the fluid diverting through the Ports.
 - The Sleeve should function within 100 – 200 psi.

	TITLE: Operating Instructions for 2-7/8" Triple Port PBL		
	Document ID DSI-GL-75-006	Revision 4	Prepared By Suraj Varma DV
	Issue Date 13-10-2013	Revision Date 09-03-2017	Approved By Gernot Bauer

- The Sleeve will return back to its original position when pumping is stopped.
5. Break the Kelly from the PBL Tool and drop 3 x **13/16"** steel De-Activation Balls into the top of the Tool.
 - Make-up Kelly to PBL Tool.
 6. Engage the pump and record the pressure at which the Activation Ball shears through the Ball Seat. **BUILD PRESSURE RAPIDLY.**
 - This should be plus or minus 10% of the recorded pressure that was sent with the Tool.
 - The shearing pressure varies from 1,600-4,500 psi. Ensure the shear pressure is suitable for the application the tool is planned to be used.
 7. With the Activation Ball sheared and the Port closed, keep pumping and lift the tool above the rotary table to visually check the Port is closed.
 8. Stop the pumps, pick up string and place in the slips
 - Break the PBL Tool between the Main Body and the Ball Catcher Sub.
 - Back out Kelly/Main Body from the string and retrieve the balls from the Ball Catcher by removing Ball Catcher Cage. **Do not under any circumstances re-use the Activation Balls once they have been used in the tool.**
 - Reinsert Ball Catcher Cage and make-up Kelly/Main Body and Ball Catcher Sub before RIH.

ACTIVATION PROCEDURE

1. Prior to activating the tool, **Record Pump Pressure** _____ **Pump Strokes** _____. This will be used as a reference to confirm de-activation of the tool.
2. Calculate the fluid displacement **volume and time** in the drill string to estimate when the Activation Ball will reach the PBL Bypass Tool.
 - Break drill string at rig floor and drop one (1) **7/8"** Activation Ball.
 - It is recommended to fill the drill string with fluid prior to dropping the Activation Ball.
3. Displace approximately 50% of the drill string volume at normal drilling pump rates then reduce the pump rate that the string pressure is 1,000 psi below the ball shearing pressure until the ball lands on the Seat.
 - In addition please consider: Flow rate should be maximum 80 gpm when ball lands on Seat.
 - **NOTE: Care should be taken when pumping the Activation Ball down as pumping the Activation Ball on Seat at high flow rates and/or pressures may cause the Activation Ball to blow through the Seat.**
 - The Activation Ball will often seat sooner than the calculated pump strokes.
 - The Activation Ball has an equivalent density of 11.2 PPG drilling fluid.

**TITLE: Operating Instructions for 2-7/8" Triple Port PBL****Document ID**
DSI-GL-75-006**Revision**
4**Prepared By**
Suraj Varma DV**Issue Date**
13-10-2013**Revision Date**
09-03-2017**Approved By**
Gernot Bauer

- In the event the ball does get blown through the Seat, as indicated by no change in pump pressure/strokes as recorded in Step 1, drop three (3) **13/16"** De-activation Balls to ensure the Activation Ball has gone through the Seat. **This step must be done prior to dropping another vinyl ball.**
 - Repeat the normal tool activation process to re-open the tool.
4. When the Activation Ball lands on Seat, the Sliding Sleeve will shift to its open position against the Spring.
- **NOTE: IT TAKES 100-200 PSI TO ACTIVATE /OPEN THE TOOL.**
 - Fluid will now be diverted through the side Ports. As long as pumping is continuous, fluid will be diverted through the Ports. If pumping is halted, the Sliding Sleeve will shift to the closed position. When pumping resumes, the Sleeve will shift open.
 - A constant, high pump rate (**6 BPM Max after activation**) should be maintained while the tool is in the open position. **If low flow rates, low differential pressures between drill pipe and annulus, bull heading, squeezing or similar low flow operations are required, it is recommended to de-activate the PBL Tool prior to commencing such operations.**

ACTIVATION DURING 'TOTAL LOSS'

In case of a vertical well, drop the Activation Ball and wait until the ball reaches the Seat by way of gravity (chasing the Activation Ball by pumping may cause the Activation Ball to blow through the Seat due to a combination of the suction caused by the loss zone and pumping).

In case of a horizontal well or highly deviated well, chase the Activation Ball with as low pumping as possible until it lands on the ball Seat.

DE-ACTIVATION PROCEDURE

1. Break the drill string at rig floor and drop 3 x **13/16"** steel De-activation Balls (It is a good practice to drop the three steel balls at an interval of 5-10 seconds after each ball is dropped)
2. After dropping the steel De-activation Balls, pump at 50% of the normal drilling flow rates and watch for a stand pipe pressure increase. When the steel balls reach the PBL Bypass Tool, they will cut off flow through the Ports creating an immediate pressure increase.
 - Bring the pressure up while continuing pumping at high constant pump rates until a pressure decrease is seen.
 - A pressure decrease is an indication the Activation Ball has blown through the Seat into the Ball Catcher. The steel balls will follow into the Ball Catcher.
 - The Activation Ball will blow through the Seat at +/- 10% of stated shear pressure depending upon downhole conditions.
 - After the Activation Ball shears through the Seat, the Sleeve will move to the closed position. Circulation will now be through the BHA.

- When pumping is resumed, check that the pressure and strokes are the same as they were prior to activating the PBL Tool (See data recorded in Step 1, above).

NOTE: After tripping out of the hole, the balls must be removed from the Ball Catcher Sub before RIH again.

The used Activation Balls should be immediately discarded and **NEVER RE-RUN**.

If the PBL Sub is to be rerun after being activated, it is strongly recommended to de-activate the tool prior to tripping out of the hole to minimize the wear within the tool.

EMERGENCY WEIGHTED DARTS WITH VINYL BALLS OR FAST DART (HOLLOW DART)

NOT AVAILABLE FOR THIS TOOL SIZE


PBL OPERATIONAL SEQUENCE



Drilling Mode
FLOW to BIT



Activation Ball
Seated



Open Position
FLOW THRU PORT



De-Activation
Balls Dropped
PRESSURE UP




Balls Sheared Thru
Seat Tool Reset



Drilling Mode
FLOW to BIT

Should there be any questions regarding the operational procedures of the PBL tool please contact a DSI representative or visit our website www.dsi-pbl.com

	TITLE: Operating Instructions for 2-7/8" Triple Port PBL		
	Document ID DSI-GL-75-006	Revision 4	Prepared By Suraj Varma DV
	Issue Date 13-10-2013	Revision Date 09-03-2017	Approved By Gernot Bauer

PBL SUB - DO's & DON'Ts

- All ID's of the drill string components should be larger than the diameter of the activation ball otherwise the ball could get stuck during the pumping process.
- If other ball-activated tools are used in the drill string (e.g. ball-activated reamer) please consider the "drift" of the PBL tool.
- Remove any "mud cleaning filters" before dropping the activation or de-activation balls.
- Be careful that no other objects (cement chunk, glove, part of a drill pipe screen, thread protector, etc.) get inside the drill pipe and land on the seat. These objects could act like an activation ball and improperly open the tool. It is highly recommended to place a filter in the standpipe and drill string to prevent unintended activation of the tool due to junk/debris.
- If the optional surface test is done, always ensure the PBL tool is fully within drilling fluids to avoid potential ball shattering during de-activation.
- Large diameter LCM materials can be pumped through the PBL ports. LCM size should not normally exceed 1/3 of port diameter (if in any doubt please call a DSI representative).
- It is recommended to pump the activation ball with a fluid spacer (normal drilling mud, no LCM included) otherwise LCM may pass the ball during the pumping process before the activation ball lands on the seat and LCM gets access to the sensitive BHA.
- When LCM has been pumped, it is recommended to clean the drill string (with normal drilling mud, no LCM included) from LCM before dropping the de-activation balls.
- Never re-use a previously dropped activation ball (vinyl).
- Once the PBL has been activated, high flow rates can be used with pressures that are much higher than the PBL de-activation pressure. DSI recommends the use of high flow rates to fully make use of the extra cleaning power of the PBL sub or high flow to pump LCM (the de-activation pressure ONLY applies when the steel balls have been dropped to de-activate the tool & cannot be exceeded by high flow rates when the tool is open).
- If low flow rates, low differential pressure between drill pipe and annulus, bull heading, squeezing or similar low flow operations are required, it is recommended to deactivate the PBL tool before commencing such operations.
- If the PBL sub is laid down and is planned to be re-run in hole, please jet-wash fully with clean water when first POOH.

Please fully use the running procedures and the tool service guidelines which are sent with each PBL tool (if in any doubt please call a DSI representative).



PBL BYPASS SYSTEMS



WORLD WIDE CONTACTS

DSI FZE

P.O. Box 30575
Dubai, UAE
Phone: +971 4 8808228
Fax: +971 4 8808218
enquiries@dsi-pbl.com

AFRICAN REGION

Jean-Luc Gagin
Regional Manager
Mobile: +33 622 584 743
jeanluc@dsi-pbl.com

AFRICA (East & South) & Angola

Johan DeKock
Business Development Manager
Phone: +27 21 976 1234
Mobile: +27 73 762 4436
johandekock@dsi-pbl.com

AFRICA (Central & West)

Hilaire Tchetnga
Business Development Manager
Phone: +237 6 94 010204
hilaire@dsi-pbl.com

ASIA PACIFIC REGION

Steve McCrone
Business Development Manager
Mobile: +60 1 2608 1960
stephenmccrone@dsi-pbl.com

CASPIAN REGION

Parviz Salimov
Business Development Manager
Mobile: +99450 2102785
psalimov@dsi-pbl.com

DUBAI

Lachlan D'sa
Operations Manager
Phone: +971 4 8808228
Mobile: +971 50 551 8930
lachlan@dsi-pbl.com

DUBAI

Suraj Varma DV
QA/QC Manager
Phone: +971 4 8808228
Mobile: +971 56 656 0397
surajvarma@dsi-pbl.com

EUROPE / UK

Alec Gwynn
Business Development Manager
Mobile: +44 7887 556 245
alecgwynn@dsi-pbl.com

EUROPE / UK

Mike Critchley
Business Development Manager
Phone: +44 1224 799600
Mobile: +44 7551 127946
mikec@dsi-pbl.com

EUROPE / INDIA

Gernot Bauer
Regional Manager
Phone: +43 2630 315 250
Mobile: +43 676 88315100
gbauer@dsi-pbl.com

INDIA

Kedar Rao
Sales
Mobile: +91 98694 43890
kedar@dsi-pbl.com

INDIA

Sarafudheen MK
Field Service Manager
Mobile: +91 94479 73136
Mobile: +971 52 983 7591 (UAE)
saraf@dsi-pbl.com

LATIN AMERICA

Martin Gonzalez
Regional Manager
Mobile: +1 915 240 4750
martingonzalez@dsi-pbl.com
martgonzalez@aol.com

MIDDLE EAST

Harris Hurst
Regional Manager
Mobile: +971 56 455 4345
harrishurst@dsi-pbl.com

MIDDLE EAST

Mohsen Al-Tamimi
Business Development Manager
Mobile: +971 50 655 0735
mohsentamimi@dsi-pbl.com

RUSSIA

Nail Khubbitdinov
Business Development Manager
Mobile: +7 912 939 68 31
nailkhubbitdinov@dsi-pbl.com
nkhubbitdinov@mail.ru

Bico Faster Drilling Tools, Inc.

Canada
21077th Street
Nisku, Alberta T9E 7YE
Phone: +1 780 955 5969
Fax: +1 780 955 4707

Bico Drilling Tools, Inc

United States,
1604 Greens Road
Houston, TX 77032
Phone: +1 281 590 6966
sales@bicodrilling.com